

# BT210



## TRUNNION MOUNTED BALL VALVE / SIDE-ENTRY / DB&B SINGLE BALL / PLATE TRUNNION



### Range of Production:

- SIZE from 10" to 36"
- PRESSURE CLASS  
ANSI 150-300-600-900-1500-2500  
API 2000-3000-5000-10000  
OTHER standard or non-standard pressure classes are optional ON REQUEST

### Standard Features:

- Split body, 3 piece construction
- Full or Reduced bore
- Bi-directional
- Soft seat
- Bubble tight seal
- Stem sealant injection
- Automatic body cavity pressure relief
- Anti-blow out stem
- Antistatic device
- Fire Safe design
- O-Ring on primary sealing - Graphite on secondary sealing
- Flanged ends (RF - RTJ)
- Drain plug
- Vent valve
- Seat sealant injection points
- Gear operated

### Available Features:

- Metal to Metal seat
- Double-piston effect seats
- Lip-seal on primary sealing
- Graphite packing on stem sealing for FET
- Locking device
- Welded or clamped ends
- Drain valve
- Extended stem
- Pneumatic actuator, single or double acting
- Hydraulic actuator
- Electric actuator
- Gas over oil
- Bare stem (top-mounting flange to ISO 5211)

